

099711-16E/650

5

UNITED STATES PATENT APPLICATION

10

OF

Won KIM, Yong Jin LIM and Byung Il JUNG

15

20

FOR

**APPARATUS FOR AUTOMATIC LOADING OF
SLEEVE ON DEVICE TESTING APPARATUS**

25

BACKGROUND OF THE INVENTION

Field of the Invention

[001] The present invention relates to a testing apparatus for testing a device, and more particularly, to an apparatus for automatic loading of a sleeve on a device testing apparatus, for automatic loading of a sleeve having a device held therein on the device testing apparatus for carrying out device test.

Background of the Related Art

[002] In general, the devices completed at a production line are subjected to test for defects before shipment. In the device testing apparatuses, there are horizontal device testing apparatuses, and vertical device testing apparatuses. The horizontal device testing apparatus makes horizontal loading of devices held in a plastic tray on a metal tray having an opened top or bottom surface, and horizontal transfer between testing steps, and tests the devices at a horizontal testing part. In the vertical device testing apparatus, upon stacking tube form of sleeves each having devices to be tested held therein on a stacker, transfer means takes, and tilts the sleeves one by one, so that the devices are dropped from the sleeve by gravity, and supplied to, and tested by, a vertical testing part in succession.

[003] Since the present invention relates to an apparatus for automatic lining up and loading of the sleeves in the vertical device testing apparatus, a system and operation of a related art vertical device testing apparatus will be explained with reference to FIG. 1 attached herein, while explanation of the horizontal device testing apparatus is omitted.

[004] Referring to FIG. 1, after stuffing devices to be tested in the sleeve 1, if the sleeves are loaded on a loader 4 in a loading part 3 in an upper part of the device testing apparatus in succession, a separate transfer device (not shown) takes the sleeves 1 one by one from a bottom of the loader 4, and transfers to a swing arm 5 which can swing to a preset

5 angle, horizontally. Then, the swing arm 5 swings to the preset angle, for an example, 45°, such that the sleeve is pushed toward the transfer track 7 by an elastic force of the spring (not shown) at rear of an insert piece 6, bringing an opening of the sleeve onto a transfer track. According to this, the devices stuffed in the sleeve are dropped from the sleeve by gravity through the opening of the sleeve, transferred to the testing part 8, and subjected to a required
10 testing at the testing part 8. The devices tested at the testing part are transferred to an unloading part 10, classified according to a test result, and put into empty sleeves 1a, and stacked at an unloading staking part 11 in succession by a transfer device (not shown).

[005] However, the related art vertical device testing apparatus requires a worker to line up and load each of the sleeves on the loader 4 at required positions thereof in succession
15 manually for loading the sleeves on the loading part 3, the loading of the sleeve has been very troublesome, with a poor working efficiency, and a subsequent poor test efficiency.

SUMMARY OF THE INVENTION

[006] Accordingly, the present invention is directed to an apparatus for automatic loading of a sleeve on a device testing apparatus that substantially obviates one or more of the
20 problems due to limitations and disadvantages of the related art.

[007] An object of the present invention is to provide an apparatus for automatic loading of a sleeve on a device testing apparatus, in which sleeves having devices to be tested held therein are loaded on the device testing apparatus, automatically.

[008] Additional features and advantages of the invention will be set forth in the
25 description which follows, and in part will be apparent from the description, or may be learned by practice of the invention. The objectives and other advantages of the invention will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

5 [009] To achieve these and other advantages and in accordance with the purpose of
the present invention, as embodied and broadly described, the apparatus for automatic loading
of a sleeve on a device testing apparatus includes a sloped loading plate for putting sleeves
each having devices held therein thereon, vertical fixation plates at both sides of the sloped
loading plate, carrier means fitted so as to be in contact with a lower edge of the sloped
10 loading plate, for holding the sleeves put on, and slid down to the lower edge of, the sloped
loading part, and transporting to a loading part in the device testing apparatus one by one in
succession, driver means fitted to the fixation plate for driving the carrier means, and return
means for, when a plurality of sleeves on the sloped loading plate are loaded on, and
transported by the step, returning the sleeves back to the sloped loading plate again, leaving
15 only one of the sleeves.

[010] It is to be understood that both the foregoing general description and the
following detailed description are exemplary and explanatory and are intended to provide
further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

20 [011] The accompanying drawings, which are included to provide a further
understanding of the invention and are incorporated in and constitute a part of this
specification, illustrate embodiments of the invention and together with the description serve
to explain the principles of the invention:

In the drawings:

25 FIG. 1 illustrates a side view of key parts of a related art vertical device testing
apparatus;

FIG. 2 illustrates a side view of key parts of a vertical device testing apparatus having
an apparatus for automatic loading of a sleeve of the present invention applied thereto;

099791-10101
TOTAL: 116E/660

5 FIG. 3 illustrates a perspective view of an apparatus for automatic loading of a sleeve in accordance with a first preferred embodiment of the present invention; and,

FIG. 4 illustrates a side view of an apparatus for automatic loading of a sleeve in FIG. 3 for showing operation thereof.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

10 [012] Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings. FIG. 2 illustrates a side view of key parts of a vertical device testing apparatus having an apparatus for automatic loading of a sleeve of the present invention applied thereto. The apparatus 100 for automatic loading of a sleeve of the present invention is mounted at one side of the
15 loading part 3 in an upper part of the device testing apparatus, for automatic lining up, and supplying sleeves 'S' stuffed with devices to be tested to the loading part 3.

[013] FIG. 3 illustrates a perspective view of an apparatus for automatic loading of a sleeve in accordance with a first preferred embodiment of the present invention.

20 [014] Referring to FIG. 3, there is a sloped loading plate 101 sloped backward in a lower part of the apparatus 100 for automatic loading for placing the sleeves thereon, and vertical fixation plates 102 on both sides of the sloped loading plate 101. There is carrier means right behind the sloped loading plate 101 for holding and transporting the sleeves on the sloped loading plate 101, and a loading standby part (not shown) in rear of the carrier means for temporary loading of the sleeves transported by the carrier means thereon for
25 standing-by until the sleeves are transported and loaded on the loading part 3 in rear of the apparatus.

[015] In the meantime, the carrier means has a system similar to a conveyer system, for transporting the sleeves slid down to a rear corner of the sloped loading plate by gravity

5 sleeves 'S' are transported upward by the conveyor belt 115 one by one automatically once the sleeves 'S' are put down on the sloped loading plate 101 by the user, the user is not required to line up the sleeves.

10 [024] In the meantime, the sleeve 'S' transported by the conveyor belt 115 is guided by the guide rails 118 as both ends of the sleeve 'S' are inserted in the guide rails 118 at top of the fixation plate 102, and dropped, lined up on a sleeve loading standby part (not shown) in rear of the apparatus in succession, and transferred to the swing arm 5 (see FIG. 2) by a separate sleeve conveyor (not shown) in rear of the apparatus for automatic loading of a sleeve. Then, the devices held in the sleeves transferred to the swing arm 5 are loaded on, and tested at the testing part 8 (see FIG. 2) according to a process as explained in the related art.

15 [025] In the meantime, when the conveyor belt 115 is in operation, the return pulley 123 of the return means at outer side of the conveyor belt rotates too, wherein if a plurality of sleeves, for an example, two sleeves, are transported with the two sleeves loaded on one step 116 on the conveyor belt 115 at a time, the projection 124 hits an upper sleeve 'S' to fall off the step 116 as the return pulley 123 rotates, and drop down onto the sloped loading plate 101, again. Thus, by the foregoing action of the return pulley 123, always only one sleeve is transferred to the loading standby part (not shown), continuously.

20 [026] Though the apparatus for automatic loading of a sleeve on a device testing apparatus 100 of the present invention is explained as applied to the device testing apparatus having a system as explained in the related art, the apparatus for automatic loading of a sleeve on a device testing apparatus 100 of the present invention can be applicable to device testing apparatuses of different systems as an individual module, once a part thereof, for an example, the conveyor device which loads sleeves at the loading standby part on a loading part of the

5 device testing apparatus is modified, appropriately.

[027] As has been explained, the automatic transportation, and loading of the sleeves onto the loading part one by one once the user puts the sleeves on the sloped loading plate 101 of the apparatus of the present invention as the user likes without lining up improves working and testing efficiencies.

10 [028] Moreover, the apparatus for automatic loading of a sleeve on a device testing apparatus of the present invention may be modified to serve to general purpose as an individual module use of which is not limited by a system of the device testing apparatus by modifying a part thereof.

15 It will be apparent to those skilled in the art that various modifications and variations can be made in the apparatus for automatic loading of a sleeve on a device testing apparatus of the present invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.